



Technical characteristics of guide rail T70

CODE	S	q ₁	e	I _{xx}	W _{xx}	i _{xx}	I _{yy}	W _{yy}	i _{yy}
	cm ²	kg/mt	cm	cm ⁴	cm ³	cm	cm ⁴	cm ³	cm
T70-1/B	9,51	7,47	2,04	41,3	9,24	2,09	18,65	5,35	1,4

Dimensions of guide rail T70

	b1	h1	h	k	n	c	f	g	r _s	m1	t1	m2	t2	d	d2	b3	l2	l3	l	l1	b2	v	q2
tolerance	+/- 1,5	+/- 0,75	+/- 0,10	0/+0,10	0		+/-0,75	+/-0,75	0/+0,06	+/- 0,10	0/-0,06	+/- 0,10				+/- 0,20	+/- 0,20	+/- 0,20	0	+/- 1,5		0/+2	
T70-1/B	70	65	64	9	34	6	8	6	2	3	3,5	2,95	3	13	26	42	105	25	128	250	70	10	1,1

Fishplates & Accessories T70

	d	b ₂	b ₃	l ₁	l ₂	l ₃	V	W _{xx}	W _{yy}	fishplate weight	Bolt size	Bolts set weight
	mm	mm	mm	mm	mm	mm	mm	cm ³	cm ³	kg/pc		kg/set
tolerance		+/- 1,5	+/- 0,20	+/- 1,5	+/- 0,20	+/- 0,20	0/+2					
T70-1/B	13	70	42	250	105	25	10	1,17	8,17	1,29	M12X35	0,51